



LAWRENCE
LIVERMORE
NATIONAL
LABORATORY

In-situ Diffraction Studies of Shock Compressed Single-Crystal Iron

D. H. Kalantar, J. D. Colvin, J. Eggert, H. Lorenzana, J. Stolken, J. Hawreliak, K. Rosolankova, J. S. Wark, M. Schneider, M. Meyers

July 22, 2004

In-situ Diffraction Studies of Shock Compressed Single-Crystal
Iron

Savannah , GA, United States

November 15, 2004 through November 19, 2004

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

In-situ Diffraction Studies of Shock Compressed Single-Crystal Iron*

Daniel H. Kalantar, J. D. Colvin, J. Eggert, H. Lorenzana, J. Stolken,
LLNL, J. Hawreliak, K. Rosolankova, J. S. Wark, University of Oxford, M.
Schneider, M. Meyers, UCSD

The technique of in-situ wide angle diffraction has been used to study materials such as Si and Cu. We have extended our studies of shocked single crystal materials to include Fe (001) that is shock compressed by direct laser irradiation using the OMEGA and Janus lasers. A series of experiments was conducted in Fe at pressures above the Hugoniot Elastic Limit. Transient x-ray was used to record the response of multiple lattice planes simultaneously. This technique of wide-angle diffraction provides information on the lattice response both parallel and oblique to the shock propagation direction. In these experiments, compressions of up to 14% in the (002) planes were observed. Details on the experiments and analysis of the dynamic lattice compression will be presented.

*This work was conducted under the auspices of the U.S. Department of Energy by the University of California Lawrence Livermore National Laboratory under Contract No. W-7405-Eng-48.